

□□□: □□□□□□□□SM□



000: 00000FI0



□□:
PU75A

FBFI750X16SB

Technische Daten			
Material	Alu-Mg-Si	Material	Alu-Mg-Si
Stärke	1,6 mm	Dichte	1,92 kg/m³
Stärke	15 mm	Temperaturbereich	-20°C...+60°C
Stärke	1...5%	Stärke	750 mm
1%Stärke	0,34 N/mm	Stärke	730 mm
1%Stärke	0,24 N/mm	Stärke	Stärke

項目	規格	試験方法
硬度	80° Shore A (±3)	80° Shore A (±3)
伸び率 (%)	0,65	0,55
密度 (g/cm³)	1,18	1,18
耐熱性	n/a	n/a
耐薬品性	耐薬品性試験SM	耐薬品性試験FI
規格	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	規格	規格
	規格	規格
	MicroClean	

REACH	EC 1907/2006
EG 1935/2004	
EG 10/2011	
UL94-HB	
not flammable	(Directive 92/69/EEC, A.10)
not flammable	FMVSS 302 (Federal Motor Vehicle Safety Standard)
FDA	(Food and Drug Administration)

Übersicht			
Temperaturbereich		Temperaturbereich	
Minimale Temperatur	155 °C	Maximale Temperatur	260°C ±10°C
Druck	0,5 bar		
Dauer	60 sek.		

[illegible]


00000000000000000000 - 10/2026

Icons

BEHAbelt icons represent the various properties and features of the product.




Complies with FDA/EC standards



Electrostatic discharge (ESD) protection




Safe for X-ray imaging (X-ray safe PU SAFE)




Antibacterial and antifungal properties



Waterproof and moisture resistant



Micro CLEAN technology for hygiene



UV-C resistant



2K (two-component) system




Vegan friendly



ISO 340 standard




Flexible and bendable



High flexibility

Applications

BEHAbelt is used in various applications:




PU and TPE material roll



PU and TPE material pieces



PU and TPE material being processed



PU and TPE material being processed



PU and TPE material being processed