



Material: **SR**



Material: **FI**



Material: **PU80A**

Material: **FBFJ750X16SB**

Technical Data

Material	Material	Material	Material
Material	1,6 mm	Material	1,92 kg/m ²
Material	15 mm	Material	-20°C...+60°C
Material	1...5%	Material	750 mm
1%Material	0,43 N/mm	Material	730 mm
1%Material	0,3 N/mm	Material	Material

Material	Material	Material
Material	84° Shore A (±3)	84° Shore A (±3)
Material μ	0,5	0,5
Material	Material	Material
Material	n/a	n/a
Material	Material SR	Material FI
Material	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
Material	Material	Material
Material	Material Rg = <10E09Ω (1GΩ)	Material Rg = <10E09Ω (1GΩ)

Material	Material
REACH EC 1907/2006	Material
EG 1935/2004	Material
IEC61340-2-3/EN61340-5-1	Material
FDA (Food and Drug Administration)	Material
Material	Material
Material	Material
Material	Material

Material


Material - 10/2026

Icons

BEHAbelt icons represent the various properties of the belts.




Belts are FDA/EC approved



Belts are static dissipative



Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



Belts are UV-C resistant



Belts are 2K (two-component) belts




Belts are vegan



Belts are ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



PU and TPE belts



PU and TPE belts