

SR: SR



FI: FI



PU65A /
PU80A

FBFJG750X2S

SR: SR

SR	SR
SR	2 mm
SR	18 mm
SR	1...5%
1%SR	0,4 N/mm
1%SR	0,28 N/mm

SR	SR2SR
SR	2,4 kg/m ²
SR	-20°C...+40°C
SR	750 mm
SR	730 mm
SR	SR

SR	SR	SR
SR	72° Shore A (±3)	84° Shore A (±3)
SR μ	0,7	0,5
SR	SR	SR
SR	0,8 mm	1,2 mm
SR	SR	SR
SR	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	SR	SR
	SR	SR = <10E09Ω (1GΩ)
	SR	2K
	SR = <10E09Ω (1GΩ)	
	2K	

SR
REACH EC 1907/2006
EG 1935/2004
IEC61340-2-3/EN61340-5-1
FDA (Food and Drug Administration)

SR	SR
SR	SR
SR	150/165 °C
SR	0,5 bar
SR	90 sek.
	260°C ±10°C

SR: SR

SR - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用橡膠帶，適用於各種工業應用。




符合FDA/EC標準



符合X光機安全標準，不含鉛，PU SAFE



具有優異之防水性能




UV-C 抗紫外線



純素製品



具有優異之彎曲性能



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2K 雙組份系統




ISO 340 標準



具有優異之彎曲性能

產品系列

提供多種規格之工業用橡膠帶




PU 及 TPE 工業用橡膠帶



PU 及 TPE 工業用橡膠帶



PU 及 TPE 工業用橡膠帶



V 型皮帶及 PU 工業用橡膠帶



PU 工業用橡膠帶