

SR



FI



PU65A / PU55D

FBFNG750X19S

SR

SR	SR
SR	1,9 mm
SR	21 mm
SR	0.5...3%
1%SR	0,82 N/mm
1%SR	0,58 N/mm

SR	SR2SR
SR	2,28 kg/m ²
SR	-30°...+60°C
SR	750 mm
SR	730 mm
SR	SR

SR	SR	SR
SR	72° Shore A (±3)	55° Shore D (±3)
SR μ	0,7	0,25
SR	SR	SR
SR	0,8 mm	1,1 mm
SR	SR	SR
SR	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	SR	SR
	SR Rg = <10E09Ω (1GΩ)	SR Rg = <10E09Ω (1GΩ)
	2K	2K

SR	SR
REACH EC 1907/2006	SR
EG 1935/2004	SR
EG 10/2011	SR
IEC61340-2-3/EN61340-5-1	SR
FDA (Food and Drug Administration)	SR

SR


SR - 10/2026

Icons

BEHAbelt icons represent the various properties and features of the belts.




Complies with FDA/EC standards



Electrostatically dissipative



Safe for X-ray and PU SAFE




Antibacterial



Waterproof



Micro Clean



UV-C resistant



2K




Vegan



ISO 340




Curved belt



Curved belt

Applications

Applications of BEHAbelt belts:




PU and TPE belt



PU and TPE belt



PU and TPE belt



PU and TPE belt



PU and TPE belt