

□□□: □□□**LGB**□



000: 00000FI0



□□:
PU65A / PU80A

□□:
FBFGJ750X22S

Technische Daten			
Material	Aluminium	Material	Aluminium 2024-T3
Stärke	2,2 mm	Dichte	1,44 kg/m³
Stärke	18 mm	Temperaturbereich	-20°C...+60°C
Stärke	1...5%	Stärke	750 mm
1% Stabilität	0,47 N/mm	Stärke	730 mm
1% Stabilität	0,33 N/mm	Stärke	700 mm

項目	規格	単位
硬度（ Shore A ）	72° Shore A (±3)	84° Shore A (±3)
伸び率 μ	n/a	0,5
厚さ	0,5 mm	0,5 mm
厚さ公差	±0,1 mm	±0,1 mm
色	黒色LGB	FDA (Food and Drug Administration)
試験方法	FDA (Food and Drug Administration)	試験方法
	試験方法	2K
	試験方法	
	試験方法	
	MicroClean	
	2K	

REACH (EC 1907/2006)

EG 1935/2004

FDA (Food and Drug Administration)

[illegible][illegible]

□□□□□□□□□□□□□□ - 10/2026

BEHAbelt

BEHAbelt 提供多種規格之工業用帶，適用於各種工業應用。




符合 FDA/EC 標準



符合 X 光機安全標準 PU SAFE



具有優異之防水性能




UV-C 光線耐性



符合 VEGAN 標準



具有多種規格之工業用帶



具有優異之導電性能



具有優異之抗菌性能




具有優異之清潔性能



2 層結構之工業用帶




ISO 340 標準



具有多種規格之工業用帶

產品系列

提供多種規格之工業用帶




PU 及 TPE 工業用帶



PU 及 TPE 工業用帶



PU 及 TPE 工業用帶



具有優異之導電性能之 PU 工業用帶



PU 工業用帶