



RI



(ID)



PU80A

FBFJ750X20SJ

Technical Data

Thickness	2 mm	Weight	2,4 kg/m ²
Reinforcement	20 mm	Temperature Range	-20°C...+60°C
Reinforcement Content	1...5%	Width	750 mm
1% Reinforcement	0,44 N/mm	Height	730 mm
1% Reinforcement	0,38 N/mm	Length	

Property	RI	(ID)
Shore A Hardness	84° Shore A (±3)	84° Shore A (±3)
Permeability μ	0,4	0,45
Color		
Reinforcement	n/a	n/a
Surface	RI	(ID)
Approval	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
Cleanability		MicroClean

REACH/EC 1907/2006
EG 1935/2004
FDA (Food and Drug Administration)

Technical Data			
Temperature	160 °C	Temperature	260°C ±10°C
Pressure	0,5 bar		
Time	60 sek.		

BEHAbelt is a registered trademark of BEHA Innovation GmbH. All rights reserved. The information provided here is for informational purposes only and does not constitute an offer or a contract. The information is subject to change without notice.


Version: 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative




Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



UV-C resistant



2-component system




Belts are vegan



ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



V-belt PU



PU belts