



SR: 100%SR



FI: 100%FI



PU:

PU55D

FBF:

FBFN750X15S

SR: 100%SR

SR	SR
SR	1,5 mm
SR	21 mm
SR	0.5...3%
1%SR	0,96 N/mm
1%SR	0,68 N/mm

SR	SR
SR	1,92 kg/m ²
SR	-30°...+60°C
SR	750 mm
SR	730 mm
SR	SR

SR	FI	FI
SR	55° Shore D (±3)	55° Shore D (±3)
SR	0,25	0,25
SR	SR	SR
SR	n/a	n/a
SR	SR	SR
SR	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
SR	SR	SR
SR	SR	SR

SR
REACH/EC 1907/2006
EG 1935/2004
EG 10/2011
IEC61340-2-3/EN61340-5-1
FDA (Food and Drug Administration)

SR	FI
SR	SR
SR	205 °C
SR	260°C ±10°C
SR	90 sek.

SR: 100%SR


SR: 100%SR - 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative




Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



Belts are UV-C resistant



Belts are 2K (two-component) belts




Belts are vegan



Belts are ISO 340 certified




Belts are curved



Belts are curved

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



Belts with V-belt profile and PU



PU belts