

000: Supergrip (ESG)



□□□: □□□□□SR□



□□:
PU75A

FBFI750X40LA

Technische Daten			
Material	Aluminium	Farbe	Weiss
Stärke	4,0 mm	Gewicht	3,6 kg/m²
Profilhöhe	40 mm	Temperaturbereich	-30°C...+50°C
Druckvermögen	1...5%	Einbauhöhe	750 mm
1%Druckvermögen	0,58 N/mm	Einbautiefe	700 mm
1%Druckvermögen	0,41 N/mm	Einbaubereich	

項目	規格	規格
硬度	80° Shore A (±3)	80° Shore A (±3)
伸び率 μ	n/a	0,55
色	黒色	黒色
重量	n/a	n/a
特徴	Supergrip (ESG)	SR
承認	FDA (Food and Drug Administration)	FDA (Food and Drug Administration)
	米国	米国
	米国	米国
	米国	米国
	米国	米国

□□□
REACH□EC 1907/2006□□□□□
EG 1935/2004□□□□□
EG 10/2011□□□□□
FDA (Food and Drug Administration)

[illegible][illegible]


00000000000000000000 - 10/2026

Icons

BEHAbelt icons represent various properties and certifications of the belts.




Belts are FDA/EC approved



Belts are static dissipative




Belts are X-ray safe (PU SAFE)




Belts are microorganism resistant



Belts are water resistant



Belts are micro clean



UV-C resistant



2-component system




Belts are vegan



ISO 340 certified




Belts are flexible



Belts are flexible

Applications

Belts are used in various applications.



PU and TPE belts



PU and TPE belts



PU and TPE belts



PU and TPE belts V-belt



PU belts