BEHAbelt
Made in Germany

Ridge top V-belt

2C, PU75A / PU80A white/transparent, reinforced Aramid



Order No.	Profile dimension	Cross section	approx. weight	Standard Roll		Recommended Min. pulley ∅		Fmax/belt (Standard)	
	mm	cm²	kg/100 m	m	ft	mm	inch	kg	lbs
FBZSP85A17K2	17 x 19	2,0	24,4	30	100	170	6,8	48,0	105,6
FBZSP85A22K2	22 x 25	3,5	42,3	30	100	210	8,4	84,0	184,8

approx. 80/84° Shore A

Recommended pretension: 0,5...2 %, **Coeff. of friction µ:** Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30

Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms

BEHA Innovation GmbH
In den Engematten 16 · 79286 Glottertal/Germany · Tel.: +49 7684 9070 · Fax: +49 7684 907101 · info@behabelt.com · www.behabelt.com