

Can Cables

PU95A red slightly rough, reinforced Aramid



approx. 95° Shore A

Order No.	Diameter Ø		Cross section cm²	approx. weight kg/100 m	Standard roll		Recommended Min. pulley Ø*		Fmax/belt (Standard)		Fmax/belt (Overlap)	
	mm	inch			m	ft	mm	inch	kg	lbs	kg	lbs
FBRN095RMA	9,5	3/8	0,71	8,5	152	500	175	6,9	35,5	78,1	210	462

Recommended pretension 0,5...2 %, **Coeff. of friction μ :** Steel: approx. 0,40 | PE: approx. 0,25 | HDPE: approx. 0,20

*Overlap +30%; ★ Crimp sleeve connection / connection set and tool on page 109.

Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.