Can cables

PU95A red slightly rough, reinforced Aramid



approx. 95° Shore A

Order No.	Diameter ∅		Cross section	approx. weight	Standard Roll		Recommended Min. pulley ∅*		Fmax/belt (Standard)		Fmax/belt (overlap)	
	mm	inch	cm^2	kg/100 m	m	ft	mm	inch	kg	lbs	kg	lbs
FBRN095RMA	9,5	3/8	0,71	8,5	152	500	175	6,9	35,5	78,1	210	462

Recommended pretension 0,5...2 %, **Coeff. of friction µ:** Steel: approx. 0,40 | PE: approx. 0,25 | HDPE: approx. 0,20

Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms

BEHA Innovation GmbH
In den Engematten 16 · 79286 Glottertal/Germany · Tel.: +49 7684 9070 · Fax: +49 7684 907101 · info@behabelt.com · www.behabelt.com