


V-guides

PU60A ultramarine blue V-guide smooth

BEST SUITABLE FOR BELT QUALITY **PU80A**












Order No.		Profile dimension	Standard Roll		Recommended Min. pulley \varnothing			
unnotched	notched	mm	m	ft	unnotched		notched	
					mm	inch	mm	inch
FBKF6YLGE	FBKF6YLGf	6 x 4 (Y)	150	492	25,0	1,0	20,0	0,8
FBKF8MLGE	FBKF8MLGf	8 x 5 (M)	150	492	30,0	1,2	25,0	1,0
FBKF10ZLGE	FBKF10ZLGf	10 x 6 (Z)	150	492	40,0	1,6	30,0	1,2
FBKF13ALGE	FBKF13ALGf	13 x 8 (A)	150	492	60,0	2,4	45,0	1,8
FBKF17BLGE	FBKF17BLGf	17 x 11 (B)	100	328	80,0	3,2	60,0	2,4
FBKF22CLGE	FBKF22CLGf	22 x 14 (C)	50	164	110,0	4,4	85,0	3,3

approx. 65° Shore A

Coeff. of friction μ : Steel: approx. 0,85 | PE: approx. 0,50 | HDPE: approx. 0,45

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.