


T-Profile

T-Profile PU65A ultramarine blue smooth (9,5 x 3,5 mm)



approx. 72° Shore A

| Order No. | Profile dimension | Cross section cm ² | approx. Weight kg/100 m | Standard Roll | | Recommended Min. pulley Ø | | Fmax/belt (Standard) | |
|-------------|-------------------|----------------------------------|----------------------------|---------------|-----|---------------------------|------|----------------------|-----|
| | mm | | | m | ft | mm | inch | kg | lbs |
| FBTG95X35LA | 9,5 x 3,5 | 0,20 | 2,4 | 30 | 100 | 20 | 0,8 | 2,9 | 6,4 |



Recommended pretension: 4...8 %, **Coeff. of friction μ** : Steel: approx. 0,75 | PE: approx. 0,50 | HDPE: approx. 0,45

FDA/EC/USDA compliant

Symbols

| | | | | | | | | |
|--|---|--|--------------------------|---|--|--|---|---|
| | | | | | | | | |
| Antistatic profile with outstanding mechanical properties. | Profile with exceptional low-temperature flexibility down to -30°C. | Patented material formulation „PLUS“ for lower product elongation. | Very good UV resistance. | FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformity for smooth profiles. | | Metal and X-ray detectable profiles for maximum food safety. | Hydrolysis resistance (HY). Suitable for humid environments. | Microbe-resistant materials do not provide a breeding ground for microorganisms |