BEHAbelt
Made in Germany

T-Profile

T-Profile PU65A ultramarine blue smooth (9,5 x 3,5 mm)



Order No.	Profile dimension	Cross section	approx. Weight	Standard Roll		Recommended Min. pulley ∅		Fmax/belt (Standard)	
	mm	cm²	kg/100 m	m	ft	mm	inch	kg	lbs
FBTG95X35LA	9,5 x 3,5	0,20	2,4	70	230	20	0,8	2,9	6,4



Recommended pretension: 4...8 %, **Coeff. of friction µ:** Steel: approx. 0,75 | PE: approx. 0,50 | HDPE: approx. 0,45

approx. 72° Shore A

FDA/EC/USDA compliant

Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-tempera-ture flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformi-ty for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environ-ments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms

BEHA Innovation GmbH
In den Engematten 16 · 79286 Glottertal/Germany · Tel.: +49 7684 9070 · Fax: +49 7684 907101 · info@behabelt.com · www.behabelt.com