


## V-guides

### PU70A **safe** capri blue V-guide smooth

BEST SUITABLE FOR BELT QUALITY **PU80A**












Order No.		Profile dimension	Standard Roll		Recommended Min. pulley $\varnothing$			
unnotched	notched	mm	m	ft	unnotched		notched	
					mm	inch	mm	inch
FBKF6YLGA	FBKF6YLGB	6 x 4 (Y)	150	492	30,0	1,2	25,0	1,0
FBKF8MLGA	FBKF8MLGB	8 x 5 (M)	150	492	35,0	1,4	30,0	1,2
FBKF10ZLGA	FBKF10ZLGB	10 x 6 (Z)	150	492	45,0	1,8	35,0	1,4
FBKF13ALGA	FBKF13ALGB	13 x 8 (A)	150	492	70,0	2,8	55,0	2,1
FBKF17BLGA	FBKF17BLGB	17 x 11 (B)	100	328	90,0	3,6	70,0	2,8
FBKF22CLGA	FBKF22CLGB	22 x 14 (C)	50	164	130,0	5,2	100,0	3,9

Coeff. of friction  $\mu$ : Steel: approx. 0,75 | PE: approx. 0,40 | HDPE: approx. 0,35 |

approx. 76° Shore A

FDA/EC/USDA compliant (Limited suitability EC)

### Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.