BEHAbelt
Made in Germany

V-guides

PU70A transparent V-guide smooth 8 x 3,2 mm

Order No.	Profile dimension	Standard Roll		Recommended Min. pulley ∅	
unnotched	mm	m	ft	mm	inch
FBKH8X32TG	8 x 3,2	150	492	25,0	1,0

BEST SUITABLE FOR BELT QUALITY **PU80A**

approx. 76° Shore A

Coeff. of friction μ: Steel: approx. 0,75 | PE: approx. 0,40 | HDPE: approx. 0,35 | **FDA/EC/USDA compliant***

Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-tempera-ture flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformi-ty for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environ-ments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms

BEHA Innovation GmbH
In den Engematten 16 · 79286 Glottertal/Germany · Tel.: +49 7684 9070 · Fax: +49 7684 907101 · info@behabelt.com · www.behabelt.com