


V-guides

PU70A transparent half round smooth

BEST SUITABLE FOR BELT QUALITY **PU80A**












approx. 76° Shore A

Order No.	Profile dimension mm	Standard Roll		Recommended Min. pulley \varnothing	
		m	ft	mm	inch
FBIH8X4TG	8 x 4	40	132	30	1,2
FBIH10X5TG	10 x 5	30	100	35	1,4
FBIH12X6TG	12 x 6	40	132	45	1,8
FBIH15X7TG	15 x 7	30	100	60	2,4
FBIH18X9TG	18 x 9	40	132	80	3,2

Coeff. of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35 | FDA/EC/USDA compliant

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.