


V-guides

PU75A sky blue, PU85A ultramarine blue, 22 x 8 mm

BEST SUITABLE FOR BELT QUALITY **PU75A/PU95A**



Order No.	Color	Profile dimension mm	Standard Roll		Recommended Min. pulley Ø	
			m	ft	mm	inch
FBFI22X8LG	sky blue	22 x 8	50	164	80	3,1
FBFK22X8LG	ultramarine blue	22 x 8	50	164	95	3,7










PU75A, approx. 80° Shore A

Coeff. of friction μ : Steel: approx. 0,70 | PE: approx. 0,40 | HDPE: approx. 0,35

PU85A, approx. 88° Shore A

Coeff. of friction μ : Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30

Symbols

								
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.