

Cleats











PU80A **safe** capri blue



approx. 84° Shore A

Order No.	Height (mm) H	Height (inch) H	Foot width (mm) B	Foot width (inch) B	Weight (g/m)	Min. pulley Ø		Standard roll	
						mm	inch	m	ft
FBCJ025LCUSX	25,00	1,00	12,50	0,50	154,00	60	2,4	20	65
FBCJ038LCUSX	38,00	1,50	12,50	0,50	228,00	60	2,4	20	65
FBCJ050LCUSX	50,00	2,00	12,50	0,50	302,00	60	2,4	20	65
FBCJ070LCUSX	70,00	2,75	12,50	0,50	455,00	60	2,4	20	65

Symbols

				 	 		
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms