


## Sidewalls

### PU80A sky blue











approx. 84° Shore A

FDA/EC/USDA compliant

Order No.	Height H		Wave width B	Base width B1	Pitch off waves A	Approx. weight	Standard Roll	Pulley diameter (∅)		
	mm	inch						Minimum	Recommended	Counterflex
FBVFH020L	20,00	0,79	23,00	32,00	25,40	174	100	35	70	70
FBVFH030L	30,00	1,18	23,00	32,00	25,40	220	100	55	80	110
FBVFH040L	40,00	1,57	23,00	32,00	25,40	265	100	75	90	150
FBVFH050L	50,00	1,97	23,00	32,00	25,40	310	100	80	100	160
FBVFH060L	60,00	2,36	45,00	55,00	50,80	445	100	90	110	180
FBVFH080L	80,00	3,15	45,00	55,00	50,80	544	50	125	130	250
FBVFH100L	100,00	3,94	45,00	55,00	50,80	642	50	155	160	310
FBVFH120L	120,00	4,72	45,00	55,00	50,80	741	50	170	185	340

### Symbols

							
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms