

## V-guides

### PU80A transparent special V-guide smooth 13x6,5 mm / 10x5 mm

BEST SUITABLE FOR BELT QUALITY **PU80A**












approx. 84° Shore A

Order No. unnotched	Profile dimension mm	Standard Roll		Recommended Min. pulley Ø	
		m	ft	mm	inch
FBKJ13X65TG	13 x 6,5	200	656	60,0	2,4
FBKJ10X5TG	10 x 5,0	150	492	45,0	1,8

Coeff. of friction  $\mu$ : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30 | FDA/EC/USDA compliant

### Symbols

	 -30°C	 LOW	 UV	 FDA EC	 METAL X-RAY			 2C
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms	Belt made of 2 components enables combination of hardness and features.