



T-Profiles

T-Profile PU85A (25 x 5 mm) green or white embossed (EFI) / smooth



● ○ also available: smooth

Order No.	Profile dimension mm	Cross section cm ²	approx. Weight kg/100m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBTK25X5GW01 (green, embossed)	25 x 5	0,58	7,0	50	164	50	2,0	16,0	35,2
FBSP85A25X5 (green, smooth)	25 x 5	0,58	7,0	50	164	50	2,0	16,0	35,2
FBTK25X5WW01 (white, embossed)	25 x 5	0,58	7,0	50	164	50	2,0	16,0	35,2
FBSP85A25X5A (white, smooth)	25 x 5	0,58	7,0	50	164	50	2,0	16,0	35,2



approx. 88° Shore A

Recommended pretension: 3...6 %, **Coeff. of friction μ :** Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30

Symbols

Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	Profiles with FDA/EC conformity for direct contact with food.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms	Belt made of 2 components enables combination of hardness and features.