

FDA  
EC  
USDA

  
-30°C



# PU75A himmelblau glatt Hohlrundriemen



Artikel Nr.	Durchmesser $\varnothing$		Material- querschnitt cm <sup>2</sup>	ca. Gewicht kg/100 m	Gebindegröße		Empf. Mind.- Scheiben- $\varnothing$		Fmax/Riemen (Stoß)*	
	Außen	Innen			m	ft	mm	inch	kg	lbs
FBHP75A048HI	4,8	1,8	0,147	1,8	200	656	30	1,2	3,6	7,9
FBHP75A063HI	6,3	2,5	0,261	3,2	100	328	45	1,8	6,2	13,6
FBHP75A080HI	8,0	3,2	0,420	5,1	100	328	55	2,2	10,0	22,2
FBHP75A095HI	9,5	3,8	0,600	7,2	100	328	65	2,6	14,4	31,7
FBHP75A125HI	12,5	5,2	1,020	12,4	50	164	85	3,4	24,4	53,7
FBHP75A150HI	15,0	5,2	1,560	19,0	50	164	100	4,0	37,4	82,3

ca. 80° Shore A

Empf. Vorspannung:  
verschweißt 4...8 %  
Nippelverbinder max. 3...6 %

**Reibwerte  $\mu$ :** Stahl: ca. 0,70 | PE: ca. 0,40 | HDPE: ca. 0,35 | **FDA/EC/USDA-konform**

\* = bei Reibwert  $\mu$ :0,5