


# PU85A grün glatt



Artikel Nr.	Profil- abmessung mm	Material- querschnitt cm <sup>2</sup>	ca. Gewicht kg/100 m	Gebindegröße		Empf. Mind.- Scheiben-Ø		Fmax/Riemen (Stoß)*	
				m	ft	mm	inch	kg	lbs
FBKP85A06	6 x 4 (Y)	0,19	2,3	100	328	45	1,8	6,9	15,3
FBKP85A08	8 x 5 (M)	0,32	4,0	100	328	50	2,0	11,6	25,6
FBKP85A10	10 x 6 (Z)	0,48	6,0	50	164	65	2,6	17,5	38,6
FBKP85A13	13 x 8 (A)	0,82	10,0	50	164	95	3,8	30,0	66,0
FBKP85A17	17 x 11 (B)	1,46	18,0	50	164	120	4,7	53,0	116,7
FBKP85A22	22 x 14 (C)	2,40	29,0	50	164	160	6,3	87,7	193,0
FBKP85A32	32 x 20 (D)	5,00	62,0	25	82	275	10,8	195,8	430,8

ca. 88° Shore A

Empf. Vorspannung 4...8 %

Reibwerte  $\mu$ : Stahl: ca. 0,60 | PE: ca. 0,35 | HDPE: ca. 0,30

\* = bei Reibwert  $\mu$ :0,5

verzahnte Ausführung möglich

