



PU85A smaragdgrün glatt, antistatisch-dissipativ

| Artikel Nr. | Durchmesser \varnothing | | Material- querschnitt cm ² | ca. Gewicht kg/100m | Gebindegröße | | Empf. Mind.- Scheiben- \varnothing | | Fmax/Riemen (Stoß)* | |
|--------------|---------------------------|-------|---|------------------------|--------------|-----|---|------|------------------------|-------|
| | mm | inch | | | m | ft | mm | inch | kg | lbs |
| FBRK020GGAAA | 2,0 | 5/64 | 0,032 | 0,5 | 200 | 656 | 15 | 0,6 | 1,2 | 2,7 |
| FBRK030GGAAA | 3,0 | 1/8 | 0,071 | 0,9 | 200 | 656 | 25 | 1 | 2,7 | 5,8 |
| FBRK040GGAAA | 4,0 | 5/32 | 0,126 | 1,6 | 200 | 656 | 35 | 1,4 | 4,7 | 10,3 |
| FBRK048GGAAA | 4,8 | 3/16 | 0,181 | 2,2 | 200 | 656 | 45 | 1,8 | 6,7 | 14,8 |
| FBRK050GGAAA | 5,0 | 1/5 | 0,197 | 2,4 | 100 | 328 | 50 | 2 | 7,1 | 15,7 |
| FBRK060GGAAA | 6,0 | 7/32 | 0,283 | 3,4 | 100 | 328 | 60 | 2,4 | 10,4 | 22,9 |
| FBRK063GGAAA | 6,3 | 1/4 | 0,310 | 3,8 | 100 | 328 | 65 | 2,6 | 11,4 | 25,1 |
| FBRK070GGAAA | 7,0 | 9/32 | 0,385 | 4,7 | 100 | 328 | 70 | 2,8 | 14,1 | 31,0 |
| FBRK080GGAAA | 8,0 | 5/16 | 0,500 | 6,0 | 100 | 328 | 80 | 3,2 | 18,4 | 40,4 |
| FBRK095GGAAA | 9,5 | 3/8 | 0,710 | 8,5 | 100 | 328 | 95 | 3,8 | 25,9 | 57,0 |
| FBRK100GGAAA | 10,0 | 7/16 | 0,785 | 9,4 | 50 | 164 | 100 | 4 | 28,6 | 62,8 |
| FBRK120GGAAA | 12,0 | 15/32 | 1,130 | 13,5 | 50 | 164 | 120 | 4,8 | 40,8 | 89,8 |
| FBRK125GGAAA | 12,5 | 1/2 | 1,230 | 14,8 | 50 | 164 | 125 | 5 | 44,9 | 98,7 |
| FBRK150GGAAA | 15,0 | 19/32 | 1,770 | 21,5 | 50 | 164 | 150 | 6 | 64,9 | 142,7 |

* = bei Reibwert μ :0,5

ca. 88° Shore A

Empf. Vorspannung 4...8 %

Leitwiderstand ca. $10^9 \Omega$ pro cm

ESD-tauglich

Reibwerte μ

Stahl ca. 0,60

PE ca. 0,35

HDPE ca. 0,30

